


- 1 **FLOORSTAND**
 - DUCTILE IRON
 - STAINLESS STEEL
 - NRS INDICATING A25655
 - NON-INDICATING A25650
 - OTHER _____
- 2 **HANDWHEEL**
 - MAT'L = _____
 - DIA _____
- 3 **ADJ. STEM GUIDE**
 - DUCTILE IRON
 - STAINLESS STEEL
 - SPLIT BUSHING
 - SIZE _____
 - # PER UNIT _____
- 4 **EXTENSION STEM**
 - L = _____
 - MAT'L = _____
 - DIA = _____

L = LENGTH AS MEASURED FROM THE FACE OF THE FLANGE TO THE BASE OF THE FLOORSTAND
* ACTUAL REQUIRED DIMENSIONS IN THE FIELD MAY VARY FROM THE DIMENSIONS SUPPLIED TO TROY VALVE.
BE ADVISED THAT FIELD ADJUSTMENTS MAY BE REQUIRED.
- 5
 - CI YOKE COUPLING (CI Mud Valve only)
 - SS SLEEVE COUPLING (SS Mud Valve only)
- 6 **MUD VALVE**
 - CAST IRON
 - 316SS
 - SIZE _____
 - NRS A25600
 - RS A25612

TYP. OF _____ UNITS

 TROY VALVE <small>A DIVISION OF PEHN-TROY MANUFACTURING INC.</small> MANUFACTURING TRUST.	www.TroyValve.com		TITLE: Mud Valve with Floorstand		DWN. TE
	PHONE: 1-570-297-2125	MAT'L: N/A	PART NO: FSA-1		PAGE:
<small>13B- DO NOT SCALE DRAWING</small>		DATE: 5/15/2020			