



TYP. OF \_\_\_\_\_ UNITS

- 1 **FLOORSTAND**
  - RISING STEM A25650 (w/Cover Tube)  
(No Flst Indication)
  - NRS W/FLST INDICATION A25655
  - DUCTILE IRON  304SS  316SS
  
- 2 **HANDWHEEL**
  - MAT'L = \_\_\_\_\_  DIA \_\_\_\_\_
  
- 3 **BEVEL GEAR MODEL**
  - By Others  By Troy Valve
  - Model: \_\_\_\_\_
  
- 4 **FLOORSTAND MOUNTING BRACKET**
  - DUCTILE IRON (A - FLUSH ONLY)
  - SS FABRICATED  304SS  316SS
  - FLUSH (A)  TOP OF FLOOR (B)
  
- 5 **ADJ. STEM GUIDE**
  - DUCTILE IRON  STAINLESS STEEL
  - SPLIT BUSHING
  - SIZE \_\_\_\_\_ # PER UNIT \_\_\_\_\_
  
- 6 **EXTENSION STEM**
  - L = \_\_\_\_\_
  - MAT'L = \_\_\_\_\_ DIA = \_\_\_\_\_
  - L = LENGTH AS MEASURED FROM THE FACE OF THE FLANGE TO THE BASE OF THE FLOORSTAND
  - \* ACTUAL REQUIRED DIMENSIONS IN THE FIELD MAY VARY FROM THE DIMENSIONS SUPPLIED TO TROY VALVE. BE ADVISED THAT FIELD ADJUSTMENTS MAY BE REQUIRED.
  
- 7  CI YOKE COUPLING (CI Mud Valve only)  
 SS SLEEVE COUPLING (SS Mud Valve Only)
  
- 8 **MUD VALVE**
  - CAST IRON  316SS
  - SIZE \_\_\_\_\_
  - NRS A25600  RS Sliding A25600\_SL



www.TroyValve.com

PHONE: 1-570-297-2125

35E- DO NOT SCALE DRAWING

TITLE:

Bevel Gear F/S For Mud Valve Offset Bkt.

MAT'L:

N/A

PART NO:

ESBGOB-2

DATE:

12/29/2021

DWN.

TE

PAGE: