



- 1 **FLOORSTAND**
 - RISING STEM A25650 (w/Cover Tube)
(No Flst Indication)
 - NRS W/FLST INDICATION A25655
 - DUCTILE IRON
 - 304SS 316SS
- 2 **HANDWHEEL**
 - MAT'L = _____
 - DIA _____
- 3 **BEVEL GEAR MODEL**
 - By Others By Troy Valve
 - Model: _____
- 4 **ADJ. STEM GUIDE**
 - DUCTILE IRON
 - STAINLESS STEEL
 - SPLIT BUSHING
 - SIZE _____
 - # PER UNIT _____
- 5 **EXTENSION STEM**
 - L = _____
 - MAT'L = _____ DIA = _____
 - L = LENGTH AS MEASURED FROM THE FACE OF THE FLANGE TO THE BASE OF THE FLOORSTAND
 - * ACTUAL REQUIRED DIMENSIONS IN THE FIELD MAY VARY FROM THE DIMENSIONS SUPPLIED TO TROY VALVE. BE ADVISED THAT FIELD ADJUSTMENTS MAY BE REQUIRED.
- 6 CI YOKE COUPLING (CI Mud Valve only)
- SS SLEEVE COUPLING (SS Mud Valve Only)
- 7 **MUD VALVE**
 - CAST IRON
 - 316SS
 - SIZE _____
 - NRS A25600
 - RS Sliding A25600_SL

TYP. OF _____ UNITS



www.TroyValve.com

PHONE: 1-570-297-2125

245- DO NOT SCALE DRAWING

TITLE:

Bevel Gear F/S For Mud Valve Thru Floor

MAT'L: N/A

PART NO:

DATE: 3/11/2021

ESBGF-1

DWN.

TE

PAGE: