



1 FLOORSTAND

- DUCTILE IRON
- STAINLESS STEEL
- NRS INDICATING A25655
- NON-INDICATING A25650
- OTHER _____

2 HANDWHEEL

- MAT'L = _____
- DIA _____

3 FLOORSTAND MOUNTING BRACKET

- DUCTILE IRON (A - FLUSH ONLY)
- SS FABRICATED 304SS 316SS
- FLUSH (A) TOP OF FLOOR (B)

4 ADJ. STEM GUIDE

- DUCTILE IRON
- STAINLESS STEEL
- SPLIT BUSHING

SIZE _____
 # PER UNIT _____

5 EXTENSION STEM

L = _____
 MAT'L = _____ DIA = _____

L = LENGTH AS MEASURED FROM THE FACE OF THE FLANGE TO THE BASE OF THE FLOORSTAND
 * ACTUAL REQUIRED DIMENSIONS IN THE FIELD MAY VARY FROM THE DIMENSIONS SUPPLIED TO TROY VALVE. BE ADVISED THAT FIELD ADJUSTMENTS MAY BE REQUIRED.

6 CI YOKE COUPLING (CI Mud Valve only)

- SS SLEEVE COUPLING (SS Mud Valve Only)

7 MUD VALVE

- CAST IRON 316SS
- SIZE _____
- NRS A25600 RS A25612

TYP. OF _____ UNITS



www.TroyValve.com

PHONE: 1-570-297-2125

130- DO NOT SCALE DRAWING

TITLE:

Mud Valve with Floorstand and Mounting Bracket

MAT'L:

N/A

PART NO:

FSA-2

DATE:

5/14/2020

DWN.

TE

PAGE: