	(1)				
		_	4SS 🗌 316SS		
	NRS Indicat				
		🗆 Non-Indicatir	Non-Indicating A25650		
		☐ Other			
	FLOOR	/	DIA =		
		<u> </u>			
A					
		SIZE			
3		_ # PER UNIT	<u></u>		
		)			
	В		DIA =		
			_ Top of Floor to U-Joint	[	
	-(4)	B =	_ U-Joint to U-Joint		
		C =	_ U-Joint to Flange Elev		
	5	* ACTUAL REQUIRE IN THE FIELD MAY DIMENSIONS SUPP VALVE. BE ADVISE ADJUSTMENTS MA	VARY FROM THE LIED TO TROY D THAT FIELD		
	5	<u>U-JOINTS</u>			
		QTY =			
	, C	MAT'L =			
		DIA =			
			OUPLING (CI Mud Valve only)		
SS SLEEVE COUPLING (SS Mud Valve only)					
7 (7) <u>MUD VALVE</u>					
□ CAST IRON □ 316 STAINLESS STEEL					
		SIZE			
TYP. OF		□ NRS A2560	0 🛛 RS A25612		
	www.TroyValve.com	TITLE: Mud Valve with Thru	Floor Floorstand and U-Joints	DWN.	
A DIVISION OF PENN-TROY MANUFACTURING INC.	PHONE: 1-570-297-2125	<sup>MAT'L:</sup> N/A	PART NO:	PAGE:	
MANGFACTORING TRUST.	20E- DO NOT SCALE DRAWING	DATE: 3/1/2021	ESUJ-3		