



1 A25650 FLOORSTAND W/POSITION INDICATOR

- DUCTILE IRON
- 304SS 316SS

2 POSITION INDICATOR

URNS TO OPEN _____

3 HANDWHEEL

- MAT'L = _____
- DIA _____

4 FLOORSTAND MOUNTING BRACKET

- DUCTILE IRON (A - FLUSH ONLY)
- SS FABRICATED 304SS 316SS
- FLUSH (A) TOP OF FLOOR (B)

5 ADJ. STEM GUIDE

- DUCTILE IRON
 - STAINLESS STEEL
 - SPLIT BUSHING
- SIZE _____
- # PER UNIT _____

6 EXTENSION STEM

L = _____

MAT'L = _____ DIA = _____

L = LENGTH AS MEASURED FROM THE FACE OF THE FLANGE TO THE BASE OF THE FLOORSTAND
 * ACTUAL REQUIRED DIMENSIONS IN THE FIELD MAY VARY FROM THE DIMENSIONS SUPPLIED TO TROY VALVE.
 BE ADVISED THAT FIELD ADJUSTMENTS MAY BE REQUIRED.

7 CI YOKE COUPLING (CI Mud Valve only)

- SS SLEEVE COUPLING (SS Mud Valve Only)

8 MUD VALVE - NRS A25600

- CAST IRON
 - 316SS
- SIZE _____

TYP. OF _____ UNITS



www.TroyValve.com

PHONE: 1-570-297-2125

24E- DO NOT SCALE DRAWING

TITLE:

Mud Valve with PI Floorstand and Mounting Bracket

MAT'L: N/A

DATE: 3/12/2021

PART NO:

FSAPI-5

DWN.

TE

PAGE: