



TYP. OF _____ UNITS

1

FLOORSTAND

- DI 304SS 316SS
- NRS Indicating A25655
- Non-Indicating A25650
- Other _____

2

HANDWHEEL

MAT'L = _____ DIA = _____

3

FLOORSTAND MOUNTING BRACKET

- Ductile Iron (A - Flush Only)
- SS Fabricated 304SS 316SS
- Flush (A) Top of Floor (B)

4

ADJ. STEM GUIDE

- DI SS SPLIT BUSHING
- SIZE _____
- # PER UNIT _____

5

EXTENSION STEM

MAT'L = _____ DIA = _____

- A** = _____ Top of Bracket to U-Joint
- B** = _____ U-Joint to U-Joint
- C** = _____ U-Joint to Flange Elev.

* ACTUAL REQUIRED DIMENSIONS IN THE FIELD MAY VARY FROM THE DIMENSIONS SUPPLIED TO TROY VALVE. BE ADVISED THAT FIELD ADJUSTMENTS MAY BE REQUIRED.

6

U-JOINTS

QTY = _____
MAT'L = _____ DIA = _____

7

- CI YOKE COUPLING (CI Mud Valve only)
- SS SLEEVE COUPLING (SS Mud Valve only)

8

MUD VALVE

- CAST IRON 316 STAINLESS STEEL
- SIZE _____
- NRS A25600 RS A25612



www.TroyValve.com

PHONE: 1-570-297-2125

20F- DO NOT SCALE DRAWING

TITLE:

Mud Valve with Floorstand, Mounting Bracket, and U-Joints

MAT'L: N/A

DATE: 3/1/2021

PART NO:

ESUJ-4

DWN.

TE

PAGE: