[<u>-</u>	1	□ Operating Nut □ Handwheel	
	$\overline{}$	☐ Cast Iron ☐ Stainless Steel	
		H.W. Diameter	
	(2)	ADJ. STEM GUIDE	
A		☐ DUCTILE IRON	
	2	☐ STAINLESS STEEL	
		☐ SPLIT BUSHING	
		SIZE	
		# PER UNIT	
	(3)	EXTENSION STEM	
В		MAT'L = DIA =	
		A = Top of H.W. or Nut to U-Join	ıt
		B = U-Joint to U-Joint	
	4	C = U-Joint to Flange Elev.	
		* ACTUAL REQUIRED DIMENSIONS IN THE FIELD MAY VARY FROM THE DIMENSIONS SUPPLIED TO TROY VALVE. BE ADVISED THAT FIELD ADJUSTMENTS MAY BE REQUIRED.	
		<u>U-JOINTS</u>	
		QTY =	
		MAT'L =	
		DIA =	
	5	☐ CI YOKE COUPLING (CI Mud Valve only)	
		SS SLEEVE COUPLING (SS Mud Valve only)	
	$\begin{array}{c} \boxed$	MUD VALVE	
	6	☐ CAST IRON ☐ 316 STAINLESS STEEL	
		SIZE	
		□ NRS A25600	
TYP. OF	UNITS	☐ RS A25612	
TED COVIDED IN	www.TroyValve.com	1 – .	VN.
A DIVISION OF PENN-TROY MANUFACTURING INC.	•	IMAT'I · IDADT NO I DA	E GE:
MANUFACTURING TRUST.	PHONE: 1-570-297-2125 20D- DO NOT SCALE DRAWING	DATE: 3/1/2021 ESUJ-2	