



- 1 **OPERATING NUT** **HANDWHEEL**
 CI SS
 H.W. DIAMETER _____
- 2 **POSITION INDICATOR WITH INTERNAL STEM & SLEEVE COUPLING**
 _____ TURNS TO OPEN
- 3 **OFFSET FLOORSTAND**
 STEEL
 304SS 316SS
- 4 **ADJ. STEM GUIDE**
 DUCTILE IRON
 STAINLESS STEEL
 SPLIT BUSHING
 SIZE _____
 # PER UNIT _____
- 5 **EXTENSION STEM**
 L = _____
 MAT'L = _____
 DIA = _____
 L = LENGTH AS MEASURED FROM THE FACE OF THE FLANGE TO THE TOP OF THE HANDWHEEL OR OP NUT
 * ACTUAL REQUIRED DIMENSIONS IN THE FIELD MAY VARY FROM THE DIMENSIONS SUPPLIED TO TROY VALVE. BE ADVISED THAT FIELD ADJUSTMENTS MAY BE REQUIRED.
- 6 **CI YOKE COUPLING**
 (CI Mud Valve only)
 SS SLEEVE COUPLING
 (SS Mud Valve only)
- 7 **MUD VALVE - NRS A25600**
 CAST IRON
 316 STAINLESS STEEL
 SIZE _____

TYP. OF _____ UNITS



www.TroyValve.com

PHONE: 1-570-297-2125

250- DO NOT SCALE DRAWING

TITLE:

Mud Valve with PI Offset Floorstand

MAT'L:

N/A

DATE:

3/12/2021

PART NO:

FSAPI-7

DWN.

TE

PAGE: