


- 1 **OPERATING NUT** **HANDWHEEL**
 CAST IRON
 STAINLESS STEEL
 H.W. DIAMETER _____
- 2 **OFFSET FLOORSTAND**
 STEEL
 STAINLESS STEEL
- 3 **ADJ. STEM GUIDE**
 DUCTILE IRON
 STAINLESS STEEL
 SPLIT BUSHING
 SIZE _____
 # PER UNIT _____
- 4 **EXTENSION STEM**
 L = _____
 MAT'L = _____
 DIA = _____
 L = LENGTH AS MEASURED FROM THE FACE OF THE FLANGE TO THE TOP OF THE HANDWHEEL
 * ACTUAL REQUIRED DIMENSIONS IN THE FIELD MAY VARY FROM THE DIMENSIONS SUPPLIED TO TROY VALVE. BE ADVISED THAT FIELD ADJUSTMENTS MAY BE REQUIRED.
- 5 CI YOKE COUPLING
 (CI Mud Valve only)
 SS SLEEVE COUPLING
 (SS Mud Valve only)
- 6 **MUD VALVE**
 CAST IRON
 316 STAINLESS STEEL
 SIZE _____
 NRS A25600 RS A25612

TYP. OF _____ UNITS

 TROY VALVE <small>A DIVISION OF PEHN-TROY MANUFACTURING INC.</small> MANUFACTURING TRUST.	www.TroyValve.com		TITLE: Mud Valve with Offset Floorstand		DWN. TE
	PHONE: 1-570-297-2125	MAT'L: N/A	PART NO: ES-4		PAGE:
<small>13E- DO NOT SCALE DRAWING</small>		DATE: 5/15/2020			