

1 **GROUND POSITION INDICATOR WITH FLOORBOX**

TURNS TO OPEN _____

2 **ADJ. STEM GUIDE**

- DUCTILE IRON
- STAINLESS STEEL

DI SPLIT BUSHING
 SIZE _____
 # PER UNIT _____

3 **EXTENSION STEM**

L = _____
 MAT'L = _____
 DIA = _____

L = LENGTH AS MEASURED FROM THE FACE OF THE FLANGE TO THE TOP OF THE OPERATING NUT

* ACTUAL REQUIRED DIMENSIONS IN THE FIELD MAY VARY FROM THE DIMENSIONS SUPPLIED TO TROY VALVE. BE ADVISED THAT FIELD ADJUSTMENTS MAY BE REQUIRED.


4 CI YOKE COUPLING
 (CI Mud Valve only)

SS SLEEVE COUPLING
 (SS Mud Valve only)

5 **MUD VALVE - NRS A25600**

CAST IRON
 316 STAINLESS STEEL
 SIZE _____

TYP. OF _____ UNITS

 TROY VALVE <small>A DIVISION OF PEHN-TROY MANUFACTURING INC.</small> MANUFACTURING TRUST.	www.TroyValve.com	TITLE: Mud Valve with Position Indicator		DWN. TE
	PHONE: 1-570-297-2125	MAT'L: N/A	PART NO: ESPI-1	PAGE:
<small>13F- DO NOT SCALE DRAWING</small>	DATE: 5/21/2020			